OptiBPM Installation

1 Introduction

This document describes the installation procedure for OptiBPM on a client computer and configuration of the License Manager on a server computer.

This document is intended for system administrators.

Before you begin, it is recommended to uninstall any older versions of OptiBPM to prevent possible conflicts.

Note:

The Licensing Hardware Key can be attached to one of the computers where the OptiBPM is installed or it can be attached to a separate computer which is intended to act as a license server.

The license server computer has to be always on, otherwise the clients will not be able to obtain license to run the applications.

2 Installation of OptiBPM

Install OptiBPM on each client machine.

- Log onto the client machine as administrator.
- Insert the installation CD to the CD-Rom.
- Go to the OptiBPM 13 Setup folder.
- Run setup.exe

Optiwave 2016 Page: 1

OptiBPM Installation

3 Configuration of the License Server computer

Install the License Key Run-time Environment software (HASP Run-time) on a separate computer which is intended to act as the License Server Computer.

- Ensure you have Administrator privileges.
- Do NOT connect the hardware key to the license server computer until requested.
- Insert the installation CD to the CD-Rom.
- Double click on HASP_setup.exe, in the "HASP Runtime setup" folder.
- Follow the on-screen instructions
- Connect the hardware key to the server.
- Open the page: http://localhost:1947/ int /devices.html to verify that the hardware key is detected.

Note:

The HASP Run-time Environment uses port 1947 to communicate with local and remote components. If you use a firewall, ensure that it does not block this port.

If the client computer running the OptiBPM is used as a license server, then installation of the License Key Run-time Environment is not required. The HASP Run-time is automatically installed with the OptiBPM.

4 Accessing the License Key on a different subnet

If the license server computer and the client computers are on different subnets, then the client computer has to be configured to access the licensing services as described below:

- Open the page http://localhost:1947/ int /config.html
- Click on the tab: "Access to Remote License Managers".
- In the field "Specify Search Parameters" enter the IP address or the name of the license server.

Optiwave 2016 Page: 2